

Série large 62200 & 62300 & 63000

Série large 62200 & 62300 & 63000							
Désignation	Dimensions principales			Charges de base		Vitesses de base	
				dynamique	statique	Vitesse de référence	Vitesse limite
	d[mm]	D[mm]	B[mm]	C[kN]	C ₀ [kN]	[r/min]	[r/min]
62201-2RS1	12	32	14	6.89	3.1		15 000
62301-2RS1	12	37	17	9.75	4.15		14 000
63001-2RS1	12	28	12	5.07	2.36		17 000
62202-2RS1	15	35	14	7.8	3.75		13 000
62302-2RS1	15	42	17	11.4	5.4		12 000
63002-2RS1	15	32	13	5.59	2.85		14 000
62203-2RS1	17	40	16	9.56	4.75		12 000
62303-2RS1	17	47	19	13.5	6.55		11 000
63003-2RS1	17	35	14	6.05	3.25		13 000
62204-2RS1	20	47	18	12.7	6.55		10 000
62304-2RS1	20	52	21	15.9	7.8		9 500
62205-2RS1	25	52	18	14	7.8		8 500
62305-2RS1	25	62	24	22.5	11.6		7 500
63005-2RS1	25	47	16	11.2	6.55		9 500
62206-2RS1	30	62	20	19.5	11.2		7 500
62306-2RS1	30	72	27	28.1	16		6 300
63006-2RS1	30	55	19	13.3	8.3		8 000
62207-2RS1	35	72	23	25.5	15.3		6 300
62307-2RS1	35	80	31	33.2	19		6 000
63007-2RS1	35	62	20	15.9	10.2		7 000
62208-2RS1	40	80	23	30.7	19		5 600
62308-2RS1	40	90	33	41	24		5 000
63008-2RS1	40	68	21	16.8	11		6 300
62209-2RS1	45	85	23	33.2	21.6		5 000
62309-2RS1	45	100	36	52.7	31.5		4 500
63009-2RS1	45	75	23	20.8	14.6		5 600
62210-2RS1	50	90	23	35.1	23.2		4 800
62310-2RS1	50	110	40	61.8	38		4 300
63010-2RS1	50	80	23	21.6	15.6		5 000
62211-2RS1	55	100	25	43.6	29	10 000	4 300

62311-2RS1	55	120	43	71.5	45		3 800
62212-2RS1	60	110	28	52.7	36		4 000
62312-2RS1	60	130	46	81.9	52		3 400
62213-2RS1	65	120	31	55.9	40.5		3 600
62214-2RS1	70	125	31	60.5	45		3 400
62314-2RS1	70	150	51	104	68		3 000